



5MP H.265 Fixed Bullet Camera

Features

- H.265+
- Powerful IR LEDs
- Adjustable 3-Axis Bracket
- Video Content Analysis
- 120dB Super WDR
- Weather-proof Design
- ONVIF Profile S

TECHNICAL SPECIFICATION

Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	5M (2592x1944)
Min. Illumination	Color: 0.005Lux@F1.2 B/W: 0Lux with IR on
Shutter Time	1/100000s~1s
S/N Ratio	>55 dB
LENS	4mm@F1.4 P-Iris
Field of View	H75/D94/V56
Network	
Ethernet	1*RJ45 10M/100M Ethernet Port
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Network Storage	NAS(Support NFS, SMB/CIFS)
Event Trigger	Motion Detection, Network Disconnection, etc.
Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.
Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G

Image Setting	
WDR	120dB Super WDR
Privacy Mask	On / Off
Advanced Function	BLC, HLC, 2D DNR, 3D DNR, ROI, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed
Video Streaming	
Primary Stream	20fps@(2592x1944), 30fps@(1920x1080, 1280x960, 1280x720, 704x576)
Secondary Stream	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176)
Tertiary Stream	30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x176)
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)
Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SLL
Image Setting	Brightness/Contrast/Saturation/Sharpness/mirror
Audio	
SIP/VoIP Support	Yes, Voice & Video-over-IP
Mechanical	
IR Distance	Up to 30m
ICR	Day&Night ICR Filter Auto Switch

General	
Working Temperature	-40°C~65°C
Working Humidity	0~95%(Non-condensing)
Power Supply	PoE (802.3af)/ DC 12V±10%
Power Consumption	8.5W MAX 12W MAX (With IR on)
Housing	Vandal-proof IK10-rated Metal Housing / Up to IP67-rated for Weather-resistant Performance
Weight	825g
Dimensions	Ø76mmX239.5mm