



## 5MP H.265 Motorized Bullet Camera

### Features

- H.265+
- Powerful IR LEDs
- Adjustable 3-Axis Bracket
- Video Content Analysis
- 120dB Super WDR
- Weather-proof Design
- ONVIF Profile S

### TECHNICAL SPECIFICATION

<b>Image Sensor</b>	1/2.8" Progressive Scan CMOS
<b>Effective Pixels</b>	5M (2592x1944)
<b>Min. Illumination</b>	Color: 0.005Lux@F1.2 B/W: 0Lux with IR on
<b>Shutter Time</b>	1/100000s~1s
<b>S/N Ratio</b>	>55 dB
<b>LENS</b>	Motorized 2.7~13.5mm@F1.4 P-Iris
<b>Field of View</b>	H84°~H30°/ D105°~D37°/ V62°~V22°
<b>Network</b>	
<b>Ethernet</b>	1*RJ45 10M/100M Ethernet Port
<b>Video Compression</b>	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
<b>Network Storage</b>	NAS(Support NFS, SMB/CIFS)
<b>Event Trigger</b>	Motion Detection, Network Disconnection, etc.
<b>Event Action</b>	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.
<b>Storage</b>	Support microSD/SDHC/SDXC Card Local Storage, up to 256G

Image Setting	
<b>WDR</b>	120dB Super WDR
<b>Privacy Mask</b>	On / Off
<b>Advanced Function</b>	BLC, HLC, 2D DNR, 3D DNR, ROI, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode
<b>Video Analysis</b>	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed
Video Streaming	
<b>Primary Stream</b>	20fps@(2592x1944), 30fps@(1920x1080, 1280x960, 1280x720, 704x576)
<b>Secondary Stream</b>	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176)
<b>Tertiary Stream</b>	30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x176)
<b>Video Bit Rate</b>	16Kbps~16Mbps(CBR/VBR Adjustable)
<b>Protocol</b>	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
<b>Image Setting</b>	Brightness/Contrast/Saturation/Sharpness/mirror
Audio	
<b>SIP/VoIP Support</b>	Yes, Voice & Video-over-IP
Mechanical	
<b>IR Distance</b>	Up to 50m
<b>ICR</b>	Day&Night ICR Filter Auto Switch

General	
Working Temperature	-40°C~65°C
Working Humidity	0~95%(Non-condensing)
Power Supply	PoE (802.3af)/ DC 12V±10%
Power Consumption	8.5W MAX 12W MAX (With IR on)
Housing	Vandal-proof IK10-rated Metal Housing / Up to IP67-rated for Weather-resistant Performance
Weight	825g
Dimensions	Ø76mmX239.5mm