



ST-T20LP-64
2MP Motorized Bullet
Network Camera

Feature

- Smart Stream
- Smart IR II
- HLC
- Defog
- Integrated Cable Management
- 256G
- License Plate Recognition
- 120fps
- 3 In 1 Super WDR Pro - 140dB
- 0.002Lux Ultra Low-light

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.002Lux@F1.2 B/W: 0Lux with IR on
WDR	140dB Super WDR (Super WDR Pro is optional for Q Series)
Shutter Time	1/100000s~1s
IR Distance	Up to 120m
Day&Night	ICR Filter Auto Switch
S/N	>55dB
Max. Vehicle Speed	120km/h
Lens	
Lens	5.3~64mm, 12X Optical Zoom
Field of View	H61°~H5°/D69°~D5°/V36°~V2°
Mount	Ø14
Focus Control	Auto/Manual
Aperture	F1.6~F2.8
Iris Control	Auto
Video	
Max. Image Resolution	1920x1080
Primary Stream	120fps@(1920x1080)(Optional for Q Series), 60fps@(1920x1080, 1280x960, 1280x720, 704x576)
Secondary Stream	60fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)
Tertiary Stream	30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180)
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)
Image Setting	Brightness/Contrast/Saturation/Sharpness

Network	
Ethernet	1*RJ45 10M/100M Ethernet Port
Network Storage	NAS(Support NFS, SMB/CIFS)
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
Audio	
Audio Compression	G.711/AAC/G.722/G.726
Audio I/O	1/1
System	
Alarm I/O	1/1
Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G
Advanced Function	Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, ROI, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur
SIP/VoIP Support	Yes, Voice & Video-over-IP
Event Trigger	Black/White List, Motion Detection, Network Disconnection, External Input, Audio Alarm, etc.
Event Action	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc.
License Plate Recognition	Support
System Compatibility	ONVIF Profile S & G & T
General	
Working Temperature	-40°C~60°C
Working Humidity	0~90%(Non-condensing)
Power Supply	PoE (802.3af)/ DC 12V±10%
Power Consumption	5.5W MAX 11W MAX (With IR on)
Weather Proof	Up to IP67-rated for Weather-resistant Performance
Weight	1080g
Dimensions	134mmX126mmX285mm

ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT



sales@sortec-eu.com



www.sortec-eu.com



Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK.