



**ST-EM-8NVR**

**8CH 5MP H.265 NVR**

# FEATURES

- Support H.265/H.264

- Support ONVIF, Highprofile S, Highprofile G

- Support IPC front-end intelligent analysis:

With SLINK Mstar smart IPC: Target Count, Object Left/Lost, Area Detection, Line

Crossing With SLINK Hisilicon smart IPC: Target Count, Object Left/Lost, Area Detection,

Line Crossing, Audio Detect, Fire Detect, Scene Change, Face Detection

- Support P2P cloud service

- Instant playback under preview screen without affecting other channel preview≤

10,000 pcs face libraries can be imported.

## Technical Specification

Video & Audio Input	Network Video Input	32ch 25ch 5MP, 16ch/8ch/4ch 4K
	Bandwidth	80M
	Audio Input	Camera composite audio input
Video & Audio Output	HDMI Output	1ch HDMIM, 1ch VGA, Resolution: 1920×1080/60Hz
	Audio Output	HDMI audio
Video & Audio Coding	Video Format	H.265/H.264
	Video Resolution	4K/5M/3MP/1080P/720P
	Decode Playback	4ch 5MP, 1ch 4K
Video Management	Video / Capture Mode	Manual recording, video recording, event recording, moving detection, video recording , alarm recording, dynamic test or alarm recording, dynamic test and alarm recording
	Playback Mode	On time playback, regular playback, event playback, external file playback, log playback
	Backup Mode	Regular backup, event backup, video clip backup
HDD	Type	2*SATA
	Maximum Capacity	Each port supports MAX 8TB HDD
External Ports	Network Port	1, RJ45 10M/100M self-adaptive LAN port
	USB Port	2, 1x USB2.0 front port, 1x USB2.0 rear port
Network Management	Network Protocol	ONVIF, IPv4, UPnP , NTP, SADP, PPPoE, DHCP, etc.
Others	Power Supply	12V 3A
	Power Consumption	≤10W (without HDD)
	Working Temperature	-10°C~+65°C
	Working Humidity	10%-90%
	Dimensions	Equipment: 350mm×240mm×68mm
	Weight	N.W: 1.7KG (without HDD) Desktop
	Installation Method	installation



[sales@sensortec-eu.com](mailto:sales@sensortec-eu.com)



[www.sensortec-eu.com](http://www.sensortec-eu.com)



Sydney House, 62 Lancaster Way, Ely,  
Cambridgeshire, CB6 3NW, UK.