



ST-EM-36NVR

16CH 4K H.265 Face
Recognition POE IVR

FEATURES

- Support corresponding channel of face comparison at the same time.
- H.265/H.264 dual stream decoding, embedded Linux operating system.
- face recognition black and white list classification.
- Cameras centralized management, including Cameras parameter configuration, information export and import, real-time information acquisition and upgrade, etc.
- Support synchronous recording, remote monitoring, backup.
- Standard ONVIF, SLINK, RTSP protocol.
- Support DDNS, EMAIL, UPNP, P2P and other functions.
- double password authentication.

Technical Specification

Operating System		Embedded LINUX
Bandwidth		80M
Video Format		H.265
Video Resolution		5MP\3MP\2MP
Smart Functions		Target Count, Object Left/Lost, Electronic Fence, Line Crossing, Face Grouping List, Face Detection, Humanoid Detection, Retrograde Detection, Leave Position Detection
Record Mode		Manual, Schedule, Motion Detection, Timing, Alarm, Stop
Playback		4CH 1080P, 1CH 5MP
Backup Mode		USB Device/Network
Video, Audio and Alarm	Video Input	16CH IP Camera(3840X2160) + 16CH Preview + 16CH Playback
	Video Output	1 HDMI, 1 VGA
	Audio Input & Output	HDMI audio
Storage	HDD	2 SATA, MAX 8TB HDD
Network	Network Interface	1*RJ45 10M/100M self-adaptive LAN port
	POE	16CH, 10/100Mbps self-adaptive Ethernet port, IEEE802.3af, 52W
	Network Function	DDNS, EMAIL, UPNP, NTP, DHCP, IP Filter, PPPoE, P2P
	Smart Phone	iPhone, Android
External Ports	USB	2 USB Ports(2 USB2.0)
	Weight (without HDD)	5.7Kg
	Installation Way	Desktop Installation

Technical Specification

Others	Power Supply	DC52V 4.62A
	Power Consumption	≤10W(without HDD)
	Dimension	Equipment: 325X245X55mm, Packing: 370X95X340mm
	Weight	N.W.: 1.7Kg; With Package: 1.92Kg



sales@sensortec-eu.com



www.sensortec-eu.com



1035 Budapest, Miklós utca 13.
VIII. em. 42.