



ST-NVR4-4-T

SensorTec Outdoor NVR

Product description

SensorTec Outdoor NVR is the high speed network video recorder of the solutions that was specially developed for on-site recording tasks. Thanks to its massive outdoor enclosure with an IP65 rating, it is able to cope with even extreme weather conditions. The thermal control of the electronic components relies on a combined system of integrated heat pipes and fans, a thermoelectric peltier cooler and sunshields. The device serves the 20MP Camera and reliably performs the recording of their high-quality video streams.. The built-in Video Content Analysis functions that makes automatic traffic violation possible.

FEATURES

- Built-in Video Content Analysis functions
- Intelligent image transmission
- Semi-passive and active cooling system
- Fans and sun shields
- IP65 box-mount, outdoor enclosure
- Designed to work reliably in outdoor conditions
- Built-in RAID function
- VRM™ Fail-safe file system
- Built-in UPS

Technical Specification

| | |
|-------------------|--|
| Description | SensorTec Outdoor Network Video Recorder |
| Application | SensorTec Traffic Violation Detection solution |
| Number of Cameras | Four SensorTec 20 MP camera |
| Number of HDDs | 4 |
| CPU board | Linux Operating System 6 Cores 3.4GHz CPU Diskless operation |
| Network | 4 x 1GBit SFP+ for camera, 1 x 1GBit for monitoring |
| Network security | 1500 bit public-key RSA; User authentication |
| Storage | 4 SATA HDD VRM™ Failsafe File-system Built-in RAID function |
| Cooling system | Active cooling system Heat pipes, peltier, fan and sunshield |
| Intelligence | Integrated Video Content Analysis |
| Approvals | EN 55032:2015/AC:2016, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 50130-4:2011/A1:2015, IEC/EN 60529 IP66, IEC 60950-1 |

Electrical Specification

| | |
|---------------------------|-------------------------------------|
| Operating temperature | -30°C – 65°C |
| Supply voltage | 230 V AC |
| Inrush current | 20 A |
| Current consumption | max. 4.5 A |
| Power consumption | 200 W + 250 W cooling (max. 1000 W) |
| Humidity | up to 100% RH (condensing) |
| Protection classification | IP65 |

Mechanical Specification

| | |
|------------------------|--------------------|
| Weight | 30 kg (66.1 lbs) |
| Dimensions (W × D × H) | 440 × 232 × 672 mm |
| Package gross weight | 34 kg (75 lbs) |
| Package dimensions | 575 × 350 × 800 mm |



sales@sensortec-eu.com



www.sensortec-eu.com



Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK.