



## **ST-C302-IR**

**2Megapixel PTZ Camera**

# Features

- H.265+
- Smart IR II
- 140dB Super WDR
- Smart PTZ Motion Detection
- IR Distance up to 200m
- 255 Preset Positions
- Video Content Analysis
- 0.002Lux Ultra Low-light
- 30x Optical Zoom
- 360 Endless Pan, 0~90 Auto Flip Tilt
- ONVIF Profile S

## Technical Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	2M (1920×1080)
Illumination	Color: 0.002Lux@F1.2 B/W: 0Lux with IR on
Shutter Speed	1/100000s~1/5s
S/N Ratio	>50 dB
Field of View	H62°~H3°/D70°~D3°/V37°~V1°( 4.7 ~ 141mm )
Focal Length	4.7~141mm, @ F1.5~ F4.0 , 30x optical zoom
Zoom Speed	Approx 4s (Optical Wide-Tele)
Minimum Working Distance	10~1500mm (Wide-Tele)
Pan Range	360°endless
Pan Speed	Pan Manual Speed: 0.5°~180°/s, Pan Preset Speed: 240°/s
Tilt Range	0°~90°(Auto Flip)
Tilt Speed	Tilt Manual Speed: 0.5°~120°/s, Tilt Preset Speed: 200°/s
Proportional Zoom	Support
Preset Quantity	255
Patrol	8 Patrols, up to 48 presets each patrol
Pattern	4 Patterns
Power Loss Recovery	Support
PTZ Position Display	ON/OFF
3D positioning	Support

## Network

Ethernet	1*RJ45 10M/100M Ethernet Port
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Network Storage	NAS(Support NFS, SMB/CIFS)
Event Trigger	Motion Detection, Network Disconnection, Audio Alarm, etc.
Event Action	FTP Upload/ SMTP Upload/ SD Card Record/ SIP Phone/ PTZ Motion

## Image Setting

WDR	Super WDR up to 140dB
Privacy Mask	On / Off
Backlight Compensation	On / Off
Advanced Function	Motion Detection, HLC, 3D-DNR, ROI, Anti-fog
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting

## Video Streaming

Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576) (60fps available for -R series)
Secondary Stream	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176 )
Tertiary Stream	30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x176 )
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)
Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, PPPoE, VLAN, 802.1x
Alarm I/O	2/2
RS485	Support
Image Setting	Brightness/Contrast/Saturation/Sharpness

## Audio

SIP/VoIP Support	Yes, Voice & Video-over-IP
Audio Compression	G.711/AAC
Audio I/O	1/1

## Mechanical

IR Distance	Up to 200m
IR Angle	Auto/Manual
ICR	Day&Night ICR Filter Auto Switch

## General

Working Temperature	-30°~65°
Working Humidity	0~90%(Non-condensing)
Power Supply	35W MAX
Power Consumption	6W MAX 35W MAX
Weather Proof	Up to IP66-rated for Weather-resistant Performance
Dimensions	Φ204.8*308mm/4Kg

ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT



[sales@sensortec-eu.com](mailto:sales@sensortec-eu.com)



[www.sensortec-eu.com](http://www.sensortec-eu.com)



Sydney House, 62 Lancaster Way, Ely,  
Cambridgeshire, CB6 3NW, UK.