



ST-30R3D

Precise 3D tracking Radar up to 50km

This beauty comprises of the tracking radar and means business. Consider this: narrow beamwidth, very fast refresh rate, extreme angular accuracy, APS/VPS capabilities, C-UAS hardkill integration and all the latest tech you can think of like AESA, MHT, MIMO and FMCW.

Features

- **SOFTWARE DEFINED:** Coverage prediction , Advanced tracking , AI-powered classification , API enabled.
- **JOINT FORCES:** Integration with: ECM/C-UAS , APS/VPS , Perimeter security.
- **ST-30R3D Software Defined:** Hi-tech devices need proper software to enhance their capabilities - our 3D radars come equipped with dedicated tools that guarantee robustness, provide reliability and build trust.

The process starts with our Prediction Software which analyzes terrain and presents actionable information on optimum radar setup, locations and detection likelihood.

Integrate through API with your C2 platform.

Improve your combat readiness and effectiveness thanks to advanced AI-based tracking and classification algorithms.



Technical Specifications

DETECTION

Instrumented range

50 km

Minimum detection range

1 m

Maximum detection range

Nano UAVS, RCS 0.01 m²

10 km

Pedestrian, RCS 0.5 m²

15 km

Light vehicle, RCS 2.0 m²

25 km

Boat, RCS 5.0 m²

30 km

Low-level helicopter, RCS 5.0 m²

30 km

Range accuracy

1 m

Range resolution

3 m

Minimum/maximum target altitude

1 m/50 km

Coverage, azimuth/elevation

20°/10°

Frequency

X-Band

Technologies

AESA/MIMO

Tx output power (peak)

12 W

TRACKING AND CLASSIFICATION

Update rate

20 Hz

Technologies

MHT

Software features included in every ST-30R3D MIMO radar.

Computationally efficient Multiple Hypothesis Tracking.Tracker is used to convert single radar detection events into real targets and their motion models (tracks).

AI-powered target classification combined with traditional classification techniques.

OPERATIONS AND MAINTENANCE

Interface protocols	IEthernet
Input power	24 VDC
Power consumption	230 W
Dimensions (W x H x D, cm)	97 x 54 x 17.5
Weight	34 kg
Operation temperatures	-40°C - +85°C
Cooling method	passive
Ingress Protection	IP 66/IP 67
Enclosure	Rugged, milled aluminium, powder coated.
Mean Time Between Failure	50 000 hours
Operational availability	99%
Fault tolerant architecture	Remote monitoring, operational parameters adjustment and restart.

ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT



sales@sensortec-eu.com



www.sensortec-eu.com



Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK.